

## TLI-DN8A

### INTRODUCTION

TLI Lighting 8A Downlight Series adopts a three colour temperature switch, 3000k, 4000k and 6000k all available in the one downlight.

White, Black, Chrome surface treatment available for different applications

Triac dimmable, 0-10v dimmable and DALI dimmable versions shares great popularity by the excellent dimming effect

Application: Suitable for commercial and residential applications like offices, supermarkets, shops, schools, hotels, restaurants, workshop, warehouse, homes etc.




### PRODUCT PARAMETERS

Product model	Size	Colour temperature	Power	Input Voltage
TLI-12DN8A-03	A110 X B90 X C38mm	3000K/4000K/6000K	12W	AC100-277V AC200-240V
TLI-18DN8A-04	A145 X B114 X C45mm		18W	
TLI-25DN8A-06	A190 X B153 X C45mm		25W	
TLI-35DN8A-08	A228 X B192 X C45mm		35W	

### MECHANICAL SPECIFICATIONS

IP Rating	IP44/65
Dimming Options	DALI, DSI, 0-10V
Operating Temperature	-15c -45c
Colour	Black/White/Brushed Chrome
Construction Material	Aluminium



### PHOTOMETRIC INFORMATION

Typical Light Source Efficacy	100lm/W
CCT Colour Temperatures	3000k/4000k/6000k
Colour Rendering Index (CRI)	80/90
Beam Angle/Viewing Angle	90D

SPECIFICATIONS ABOVE ARE FOR REFERENCES ONLY AND MAY VARY WITHOUT PRIOR NOTICE