

TLI-PL9001

INTRODUCTION

TLI Lighting Extrusion series gives you flexibility in all residential and commercial applications. Offering custom lengths, Colour temperatures and finishes for any job.

Applications: Suitable for commercial and residential applications like offices, supermarkets, shops, schools, hotels, restaurants, workshop and warehouse




PRODUCT PARAMETERS

Product model:	Size:	Colour Temperature:	Power:	Input Voltage:
TLI-PL9001-Recessed	"See Diagram"	3000k, 4000k, 6000k	4.8, 9.6, 19.2W/m	DC12V-24V

MECHANICAL SPECIFICATIONS

IP Rating: IP20
 Dimming Options: DSI, Dali, 010V
 Operating Temperature: -15 to 45°C
 Inner Colour: Anodised Aluminium
 Outer Colour: Anodised Aluminium
 Construction Material: Aluminium



PHOTOMETRIC INFORMATION

CCT Colour Temperatures: 3000k, 4000k, 4000k
 Lumens: 3000k: 80lm/W 4000k: 91lm/W
 Colour Rendering Index (CRI): 80/90
 Beam Angle / Viewing Angle: 120°

PHOTOMETRIC INFORMATION

SPECIFICATIONS ABOVE ARE FOR REFERENCES ONLY AND MAY VARY WITHOUT PRIOR NOTICE

TLI-BAR2835-4.8W

PRODUCT PARAMETERS

Product model:	Size:	Colour Temperature:	Power:	Input Voltage:
TLI-BAR2835-4.8W	5M Roll	3000K, 4000k, 6000k	4.8W PM	DC12V

MECHANICAL SPECIFICATIONS

IP Rating: IP33
Dimming Options: Yes
Operating Temperature: -15 to 45°C
Construction Material: Aluminium
Warranty:2 Years
Tail Lead: 500mm



PHOTOMETRIC INFORMATION

CCT Colour Temperatures: 3000k, 4000k, 6000k
Lumens: 3000k: 350lm PM 4000k: 370lm PM 6000k: 390lm PM
Colour Rendering Index (CRI): 80+
Beam Angle / Viewing Angle: 120°



PHOTOMETRIC INFORMATION

SPECIFICATIONS ABOVE ARE FOR REFERENCES ONLY AND MAY VARY WITHOUT PRIOR NOTICE

TLI-BAR2835-9.6W

PRODUCT PARAMETERS

Product model:	Size:	Colour Temperature:	Power:	Input Voltage:
TLI-BAR2835-9.6W	5M Roll	3000K, 4000k, 6000k	9.6W PM	DC12V
TLI-BAR2835-9.6W	10M Roll	3000K, 5000k, 6000k	9.6W PM	DC24V



MECHANICAL SPECIFICATIONS

IP Rating: IP33
Dimming Options: Yes
Operating Temperature: -15 to 45°C
Construction Material: Aluminium
Warranty: 2 Years
Tail Lead: 500mm



8mm

:Diodes are 5mm Apart

PHOTOMETRIC INFORMATION

CCT Colour Temperatures: 3000k, 4000k, 6000k
Lumens: 3000k: 700lm PM 4000k: 720lm PM 6000k: 740lm PM
Colour Rendering Index (CRI): 80+
Beam Angle / Viewing Angle: 120°

PHOTOMETRIC INFORMATION

SPECIFICATIONS ABOVE ARE FOR REFERENCES ONLY AND MAY VARY WITHOUT PRIOR NOTICE

TLI-BAR2835-19.2W

PRODUCT PARAMETERS

Product model:	Size:	Colour Temperature:	Power:	Input Voltage:
TLI-BAR2835-19.2W	5M Roll	3000K, 4000k	19.2W PM	DC24V
TLI-BAR2835-19.2W	10M Roll	3000K	19.2W PM	DC24V



MECHANICAL SPECIFICATIONS

IP Rating: IP33
Dimming Options: Yes
Operating Temperature: -15 to 45°C
Construction Material: Aluminium
Warranty: 2 Years
Tail Lead: 500mm



PHOTOMETRIC INFORMATION

CCT Colour Temperatures: 3000k, 4000k
Lumens: 3000k: 1400lm PM 4000k: 1400lm PM
Colour Rendering Index (CRI): 80+
Beam Angle / Viewing Angle: 120°

PHOTOMETRIC INFORMATION

SPECIFICATIONS ABOVE ARE FOR REFERENCES ONLY AND MAY VARY WITHOUT PRIOR NOTICE